

# SPECIFICATIONS

## Audio Section

- Frequency response ..... 2 Hz - 20 kHz,  $\pm 0.5$  dB
- Harmonic distortion + noise (1 kHz) ..... 0.003 % or less
- S/N ratio ..... 105 dB or more
- Dynamic range ..... 96 dB or more
- Output voltage (1 kHz, 0 dB) .....  $2.0 \pm 0.3$  V

## Laser Diode Properties

- Material ..... GaAlAs
- Wavelength ..... 790 nm
- Laser Output ..... max. 1.23  $\mu$ W\*

\* This output is the value measured at a distance of about 200 mm from the objective lens surface on the Optical Pick-up Block.

## General

- Power requirements  
U.S.A. and Canada models ..... AC 120 V, 60 Hz  
Australia model ..... AC 240 V, 50 Hz  
Europe and U.K. models ..... AC 230 V, 50 Hz  
Asia and General models ..... AC 110-120/220-240 V, 50/60 Hz  
China model ..... AC 220 V, 50 Hz
- Operating temperature ..... +5 °C to +35 °C (+41 °F to +95 °F)
- Power consumption ..... 13 W
- Dimensions (W  $\times$  H  $\times$  D) ..... 435  $\times$  86  $\times$  260 mm
- Weight ..... 3.5 kg

Please note that all specifications are subject to change without notice.